



NOTES:

- 1.ELECTRICAL TEST:100% OPEN.SHORT & MISS WHRE TEST
- 2.CONDUCTOR RESISTANCE:5.0HMS MAX.
- 3.INSULATOR RESISTANCE:DC300V/0.01S500K OHM MN.
- 4.PRINTING WORD OF CABLE: E216040 兗 AWM2835 26AWG 60° 30V TIA/EIA 568B.2 FTP CAT.5E WELLSUN

NO.	SPECIFICATION STANDARD	QTY
⑤	PACKING BAG SIZE: 90*240*0.08MM	1
④	CABLE TIE L=100*1.85-1.9MM.	1
③	RJ45 8P8C CRYSTAL HEAD+Hulled GOLD-PLATED F U"	2
②	45P PVC MOLDING,COLOR : GREY	Kg/g
①	CAT.5E S-FTP 26AWG(7/0.16CCS)*4P+AL/ML+D OD:5.5MM+0.25/-0.2 PVC JACKET,COLOR: GREY	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

RJX2-080826C5EGE-Mxxx-LF

SERIES | LEADFREE
2M:2000mm
5M:5000mm
MALE TO MALE
08 TO 08 WAY | CAT.5e
26 AWG | GREY

DESCRIPTION: CAT.5E S-FTP FTP CABLE BLUE L=5000MM

煜倫股份有限公司

www.morethanall.com