

Technical data

- Nominal voltage: 300V/7A
PITCH:5.0mm
- Insulation Withstands Voltage:
AC 1600V/MIN
- Insulation Resistance:
1000MΩ or more at DC500V
- Using temperature range:-40℃ -115℃
Soldering temperature:260±5℃/10s
- Undimensioned Tolerances:

Dim.L=P×5.0 Dim.B=(P-1)×5.0 P= number of poles (2-12P)		
	Dim B	Dim L
0-30mm	±0.15	±0.20
over 30mm-60mm	±0.20	±0.25
over 60mm-90mm	±0.25	±0.30
over 90mm	±0.30	±0.40

6.RoHS Compliance

7.Critical dimension: Poles 02-16

3	Solder PIN	BRASS H62	TIN, PLATED	P
2	T&R COVER	PA6T UL94V-0	ALL COLOR	1
1	BODY	PA6T UL94V-0	ALL COLOR	P
ITEM	NAME OF PART	MATERIAL	NOTES	Q"TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50


.X ± 0.30

.XX ± 0.10

.XXX ±

ANG ± 1°

P PROJECTION



ORDER INFORMATION

TBN050-PV110C-xx-LF

SERIES

LEADFREE

02~16 WAY

CAP

HIGH 11.0mm

180°SMT

MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: