

Note:

1. Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Copper alloy, t=0.25mm.
- 1.3 Shell: Copper alloy, t=0.30mm.
- 1.4 Hood: Cold rolled steel, t=0.30mm.

2. Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mW Max.
- 2.4 Insulation resistance: 1000 MW Min at DC 500V.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.02 Kgf Min.
- 2.7 Temperature range: -55°C~+105°C

3. Finishes:

- 3.1 contacts: Gold flashed 1u", 3u", 5u", 10u", 15u", 30u".
- 3.2 Shell: Nickel plated.

No.	Name	Qty	Material	Remarks & Thickness	Finish
4	Hood	1	Cold rolled steel	T=0.30mm	Nickel Plated
3	Shell	1	Copper alloy	T=0.30mm	Nickel Plated
2	Contact	4	Copper alloy	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	vary

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

USB-SSCWH-4A-LF
SERIES | | | LEADFREE
| | | 4 PIN A TYPE
| | | WHITE
| | | COVER
| | | SOLDER
| | | FEMALE

DESCRIPTION: USB-A TYPE SOLDER 加外套(F)