

Recommended P.C.B Layout

## MATERIAL

Insulator : NY10T UL94-V0

Contact Pin : Brass

## SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 5000mΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20

DATE

.XXX ±


ANG ± 3°

煜倫股份有限公司

www.morethanall.com

SIZE A4

P PROJECTION



## ORDER INFORMATION

HS-V065X30-1XxxR-LF  
SERIES | HIGH 6.5mm | CONTACT 3.0mm | NON POST | LEADFREE R TYPE FOOT  
180°SMT | 1X02:02 WAY | 1X40:40 WAY

DESCRIPTION: PIN HEADER 2.54\*2.54mm SMT S/T TYPE, SINGLE ROW DUAL INSULATORS