


4	RIGHT ANGLE BNC MALE TO FEMALE CRIMP FOR CABLE (NICKEL PLATED) SHELL:ZINC, BODY:BRASS, REAR BODY:ZINC, FEMALE BODY:ZINC, INSULATOR:POM, COVER:RUBBER CONTACT PIN(PLUG): BRASS , CONTACT PIN(JACK): P-BRONZE
3	CABLE (SEE NOTE1)
2	HEAT SHRINK TUBE COLOR: BLACK
1	BNC CRIMP PLUG FOR CABLE (NICKEL PLATED) SHELL:ZINC, BODY:BRASS, INSULATOR:POM
	CONTACT PIN: BRASS
ITEM	DESCRIPTION



NOTE1:CABLE SPECIFICATION:(2.5C-2V)	
CONDUCTOR	1/0.4
INSULATOR	OD 2.4
BRAID SHIELD	16/6/0.12
JACKET	OD 4.0


RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE

0.5-15 = ±0.15
15-30 = ±0.30
30-120 = ±0.60
>120 = ±1.00
ANGLES
±5°



ORDER INFORMATION

BNCX2-1S1SU25C2V-M11C-LF
SERIES | LEADFREE
110mm
MALE TO MALE
2.5C2V
U LINK
ST/ST

www.morethanall.com

SIZE A4

PJECTION

DESCRIPTION: BNC U-link with monitor, 2.5C2V cable, 75 ohm