

电气性能:

導通阻抗:10Ω

絕緣阻抗:5MΩ

耐壓:350V

NOTES: 重點詳細說明

ITEM	MATERIAL	QUANTITY
1	UL 2651 28AWG 10P FLAT CABLE 1.0mm PITCH RED LINE	1PCS
2	10PIN IDC(2*5) SOCKET (PITCH=2.0mm)黑色無鼻 二件式	2SET
3	杜邦:2.0 2*5P HOUSING COLOR:Black MPV-H-2X05	1PCS
4	杜邦:2.0 鍍錫端子 MPV-T-26	10PCS
5	白底黑字 PAPER LABEL	1PCS

PIN ASSIGNMENT:

P1	1	2	3	4	5	6	7	8	9	10
P2	1	2	3	4	5	6	7	8	9	10

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±

PJECTION



ORDER INFORMATION

MF2MPV-10B05KX-F25C-LF

SERIES

LEADFREE  
250mm  
FEMALE TO FEMALE  
KEYLESS  
10 TO 10 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: