

Material:

- Item (a) Contact pin: Copper, Tin plated
- Item (b) Terminal (housing): Thermoplastic (UL94V-0)

Electrical: cULus

- Voltage rating: 300V
- Current rating: 8A
- Withstanding Voltage: 16 KV
- Operating temperature: -40°C to +115°C
- ▲ Soldering temperature: 260°C ± 5°C / 5 Sec
- Safety Approval: cULus
- Critical dimension: ▽

DIMENSION

Dim A	$N \times 3.81 + 2$
Dim B	$(N-1) \times 3.81$
Dim C	$(N-1) \times 3.81 + 3.9$

N= NUMBER OF POLES

Poles	Dim A	Dim B	Dim C
2P-5P	±0.15		+0.15 -0.0
6P-10P	±0.20		+0.20 -0.0
11P-15P	±0.25		+0.25 -0.0
16P-20P	±0.30		+0.30 -0.0
21P-24P	±0.35		+0.35 -0.0

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1


.XXX ±

DATE

ANG ± 1°

SIZE A4

P PROJECTION



ORDER INFORMATION

TBH038-PRB-xx-LF

SERIES | LEADFREE
| 02~24WAY
| BOX
| DIP 90°
| MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: