

SPECIFICATIONS

CURRENT RATING: 3 AMP
 INSULATION RESISTANCE: 1000M OHMS MIN.
 DIELECTRIC WITHSTANDING: 600V AC/DC
 CONTACT RESISTANCE: 20m OHMS MAX.
 OPERATING TEMPERATURE: -40 °C ~ +105 °C

MATERIALS

CONTACT MATERIAL: PHOSPHOR BRONZE
 INSULATION MATERIAL: POLYESTER, UL 94V-0 NYLON 6T

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50
 .X ± 0.35
 .XX ± 0.25
 .XXX ± 0.05
 ANG ±

P PROJECTION



ORDER INFORMATION

F-V75XC-2Xxx-LF
 SERIES | LEADFREE
 180°SMT | 2X03:06 WAY
 HIGH 7.5mm | CAP | 2X40:80 WAY
 NON POST

DESCRIPTION: 2.54mm Female Socket Dual Row SMD type (H=7.5)