

T:1.6 Dimensions of PC board holes

Tolerance : ± 0.05 (Printed-top view)

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

6	TERMINAL	2	C2680	t=0.5	Cu/Sn PLATED
5	TERMINAL	2	C2680	t=0.5	Cu/Sn PLATED
4	OUTER CONTACT	2	C2680	t=0.3	Cu/Sn PLATED
3	COVER	2	ABS		UL-94HB(BLACK)
2	WASHER	4	PBT 4815		UL-94V0
1	HOUSING	1	PBT 4815		UL-94V0(BLACK)
LTR	PART NAME	QTY	MATERIAL		REMARK

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

P PROJECTION



ORDER INFORMATION

RCAB2-JR70E1WWRR14-03-LF

SERIES JACK 7.0mm DIP 90° EAR AB: WHITE, WHITE + CD: RED, RED LEADFREE 03 WAY 14mm

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: