

P.C.Board Layout

Contact:

Contact:Brass.

Insulator:Nylon6T.

Finish:Gold flash plated over nickel.

Circuits	Dimension	
	A	B
10	5.08	9.34
12	6.35	10.61
14	7.62	11.88
16	8.89	13.15
20	11.43	15.69
24	13.97	18.23
26	15.24	19.50
30	17.78	22.04
34	20.32	24.58
40	24.13	28.39
44	26.67	30.93
50	30.48	34.74
60	36.83	41.09
64	39.37	43.63
66	40.64	44.90
68	41.91	46.17
80	49.53	53.79
100	62.23	66.49

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

PAB-V16XC-2Xxx-LF
SERIES | | LEADFREE
2X05:10 WAY
2X50:100 WAY
180°SMT | CAP
HIGH 1.6mm | NON POST

DESCRIPTION: 1.27-1.27 Pitch Box Header SMT Type