

**Material:**

- Item 1 Insulator(housing):Thermoplastic (UL 94V-0)
- Item 2 Metal housing: Steel stamping
- Item 3 Contacts:Brass
- Item 4 Terminal screw: Steel Zinc plating"-slot type

**Electrical**

- Voltage rating : 300V
- Current rating : 57A
- Wire range :
- Solid wire (AWG) : 8-22
- Stranded wire (AWG) : 8-22
- Torque (LB-In.) : 19
- Screw : M4.5
- Wire strip length : 10-11mm
- Withstanding voltage : 1.6KV
- Operating temperature : -40°C+115°C
- Soldering temperature : 250°C+10°C/5 Sec
- Safety Approval:us

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76	121.92
Dim B	10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76
TOL	±0.15						±0.20				

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION



**ORDER INFORMATION**

**TBH101-D28R-xx-LF**

SERIES | | | LEADFREE  
| | | 02-12WAY  
| | | R TYPE FOOT  
| | | HIGH 28.5mm  
| | | DIP 180°

**煜倫股份有限公司**

[www.morethanall.com](http://www.morethanall.com)

DESCRIPTION: