



A	B	C	D	COLOR	E
1				WHITE	8
2				WHITE	7
3				WHITE	6
4				WHITE	5
5				WHITE	4
	2			BLUE	3
	1			WHITE	2
		2		RED	1
		1		YELLOW	9
			1	WHITE	15
			2	WHITE	14
			3	WHITE	13
			4	WHITE	12
			5	WHITE	11
			6	WHITE	10

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL/CSA 1007 #24 WHITE	11pcs	E108485
2	WIRE:	UL/CSA 1007 #24 BLUE	1pcs	E108485
3	WIRE:	UL/CSA 1007 #24 WHITE	1pcs	E108485
4	WIRE:	UL/CSA 1007 #24 RED	1pcs	E108485
5	WIRE:	UL/CSA 1007 #24 YELLOW	1pcs	E108485
6	HOUSING:	MKL-H-08 WHITE	1pcs	E144544
7	HOUSING:	MKL-H-07 WHITE	1pcs	E144544
8	TERMINAL:	MKL-T-24	11pcs	E144544
9	HOUSING:	XH-H-02	2pcs	E149293
10	TERMINAL:	XH-T-24	4pcs	E149293
11	CONN:	DS-SS-15 SOLDER BLACK	1pcs	
12	SHRINK TUBE:	1.5φ*10mm BLACK F32	15pcs	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

DBMKLXHX122-1507080224-F15C

SERIES

150mm

FEMALE TO FEMALE

24 AWG

15/ 07/ 08/ 02 PIN

DESCRIPTION: