

PC BOARD LAYOUT

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating:3 Amperes.
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.
 Insulation Resistance:500 Medohms Minimum.at DC 500V.
 Contact Resistaance:25 Milliohms Maximum.
 Operating Temperature:-55°C to+105°C.

MECHANICAL CHARACTERISTICS:

Contact Insertion Force:341 g.Maximum.
 Contact Separation Force:21 g.Minimum.
 Grounding Screw Torque:3 Kg.Minimum.

MATERIALS:

Contacts:Brass.
 Insulator: PBT UL 94V-0 Rated.
 Shell:Cold Roller Steel.
 Grounding Screw Torque:Brass

FINISHES:

Contact:Gold Flash.
 Shell:Nickel Plated.
 Grounding Screw :Tin Plated Over Nickel Underplating


RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

X.±
 .X±
 .XX±
 .XXX±
 ANG±



ORDER INFORMATION

HDDM6-SSZJ-15-LF

SERIES | | | | | LEADFREE
 | | | | | 15 WAY
 | | | | | JACKSCREW
 | | | | | CLIP
 | | | | | SEMI GOLD
 | | | | | FEMALE

DESCRIPTION: D-SUB 15 FEMALE HIGH DENSITY STRAIGHT DIP MOUNT PLASTIC BOY 0.236"(6.00)