

7	DRIVE IC(R)	1			
6	P CONTACT	1	CU ALLOY	Au	PLATED
5	GND CONTACT	1	CU ALLOY	Au	PLATED
4	T CONTACT	1	CU ALLOY	Au	PLATED
3	R/D(A) CONTACT	2	CU ALLOY	Au	PLATED
2	COVER	1	HIGH-TEMP PLASTIC		
1	HOUSING	1	HIGH-TEMP PLASTIC		
LTR	PART NAME	QTY	MATERIAL	REMARK	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL:  $\pm 0.3$

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±


DATE

.XXX±

ANG±

SIZE A4

P PROJECTION



ORDER INFORMATION

POP-JR24-05C3R-LF

SERIES | | LEADFREE  
5P3C  
POST 2.0+4.5mm  
DIP 90°  
JACK

DESCRIPTION:  $\phi 3.5$ mm Audio Jack + SPIDF

www.morethanall.com