

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 30mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Wafer PA66,Beige UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
XHD-D-04	2.50	7.50
XHD-D-06	5.00	10.00
XHD-D-08	7.50	12.50
XHD-D-10	10.00	15.00
XHD-D-12	12.50	17.50
XHD-D-14	15.00	20.00
XHD-D-16	17.50	22.50
XHD-D-18	20.00	25.00
XHD-D-20	22.50	27.50
XHD-D-22	25.00	30.00
XHD-D-24	27.50	32.50
XHD-D-40	47.50	52.50

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

- X, ±
- X, ±
- .XX ±
- .XXX ±
- ANG ±

PPOJECTION



ORDER INFORMATION

XHD-D-xx-LF
 SERIES | LEADFREE
 04~40 WAY
 DIP 180°

DESCRIPTION: XHD 2.5 180 DIP

煜倫股份有限公司

www.morethanall.com