

**Performance:**

Meets C6 EIA/TIA 568B Standard.

**Materials:**

- Body : Fireproof ABS UL-94V0
- Metallic Case : Metal
- Jack : 8P8C 50 micro inches gold plated
- PCB : FR-4 / UL-94V0
- IDC Cap : Fireproof ABS UL-94V0
- IDC Body : Fireproof ABS UL-94V0
- IDC Pin : Bronze & Tinned

IDC Description : For 22-26 AWG.  
For 110 or Krone punch-down Tool

**Electrical Specifications:**

- Insulation Resistance : 500M ohms (min.)
- Contact Resistance : 20m ohms (max.)
- Current Rating : 1.5 Amps .
- DC Resistance : 0.1 ohms (max.)
- Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

**Mechanical Specifications:**

- IDC Punch Down Cycle : Over 250 Cycles (min.)
- Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/ mm SCALE 1:1

DATE

SIZE A4

X. ± 1  
.X ± 0.2  
.XX ± 0.15  
.XXX ±  
ANG ±

PJECTION



**ORDER INFORMATION**

MJK16C6-CWF50CV-0808-LF

SERIES | IDC | COVER | 50u" GOLD | FULL METAL | WHITE | 8P8C | LEADFREE

DESCRIPTION: C6 KEYSTONE JACK UTP 50u