



Recomended PCB Layout

### Specifications

Contact Resistance: 30m $\Omega$ max. at DC  
 100mA  
 Insulator Resistance: 1000M $\Omega$ min. at DC  
 500V  
 Current Rating: 7 AMP  
 Dielectric Withstanding  
 Voltage: AC 1000V For 1 minute  
 Operating Temperature: -55° C ~ +105° C  
 Contact: Brass  
 Housing: PBT & 30% Glass Fiber (UL  
 94V-0)

### Dimension

Positon	A	B	C
9	16.33	24.99	30.81
15	24.66	33.32	39.14
25	38.38	47.04	53.04
37	54.84	63.50	69.32

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±  
 .X±  
 .XX±  
 .XXX±  
 ANG±

PPOJECTION



### ORDER INFORMATION

DDM-S-xx-LF  
 SERIES | T LEADFREE  
 09-37WAY  
 FEMALE

DESCRIPTION: D-SUB DIP STRAIGHT TYPE W/O METAL REAR SHELL