



8	Contact Terminals	Brass	Silver Ptd.	5
7	Housing	PBT+30%GF	F202G30BK	1
6	Spring Ring	Steel	Nickel Ptd.	1
5	Set Screw	Steel	Nickel Ptd.	1
4	"T" Holder	Steel	Nickel Ptd.	1
3	Strainboot	PVC		1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

Specifications

rating : 100V AC 4A MAX
 contact resistance : pins-30mΩ MAX; shell-50mΩ MAX
 insulation resistance : MIN 100 MEGΩ @500V DC
 voltage withstand : 250V AC R.M.S. for 1 minute

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION



ORDER INFORMATION

DAMS-PA-05B-LF
 SERIES | | LEADFREE
 | | B KEY
 | | 05 WAY
 | | ASSEMBLY
 | | MALE

DESCRIPTION:

www.morethanall.com