



Contact position arrangement and specifications					
Contact configuration		Withstanding voltage	300V AC	Operating temperature range	-25c to +85c
		Voltage rating	30V AC, 42V DC	Storage temperature range	300V AC
		Current rating	2A	Insulation resistance	1000MΩ
		Contact resistance	15MΩ		
MATERIAL					
HOUSING	PPS UL94V-0/BLACK	RECEPTACLE SHELL	ZINC ALLOY	WASHER	PHOSPHOR BRONZE
CONTACT	BRASS	NUT	BRASS	O-RING	EPDM/BLACK
FINISH					
CONTACT	GOLD FLASH	RECEPTACLE SHELL	NICKEL	Internal Tooth Washers	NICKEL
NUT	NICKEL				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ± 1°

P PROJECTION



ORDER INFORMATION

DAS12-PSPBONW-12-LF

SERIES | M | A | S | 1 | 2 | P | S | P | B | O | N | W | - | 1 | 2 | - | L | F
 LEADFREE
 12 WAY
 WASHER
 NUT
 RING
 PANEL BACK
 MALE
 SOLDER

DESCRIPTION: DIN 12PIN(M) LF 線端