

FEATURE:

INSULATOR

Glass-Filled PBT is 94V-0 rated

CONTACT

Phosphor Bronze selective gold plating over nickel

SPECIFICATION:

Current Rating: 3 amperes

Contact Resistance: 21 miniohms max.

Operation Temperature: -55°C to 105°C

Voltage Rating: 800 VAC 1 minute

Insulation Resistance: 5000 megohms min

Insertion Force: 412 grams max. per pair

Withdrawal Force: 32 grams min. per pair

CONTACTS NO	DIM A	DIM B	DIM C	DIM D	DIM E
18/36	93.12	86.62	79.02	75.72	67.32
20/41	100.94	94.54	86.94	83.64	75.24
22/44	108.86	102.46	94.86	91.56	83.16
28/56	132.62	126.22	118.62	115.32	106.92
31/60	140.54	134.14	126.54	123.24	114.84
43/86	192.02	185.62	178.02	174.72	166.32
50/100	219.74	213.34	215.74	212.44	194.14

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/ mm SCALE 1:1

DATE


SIZE A4

PJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION



DESCRIPTION: