

Material:

- Item ① Insulator(lever): Thermoplastic (UL94V-0)
- Item ② Insulator(housing): Thermoplastic (UL94V-0)
- Item ③ Wire guard: Stainless steel
- Item ④ Terminal Body(contact pin): PhBz.

Electrical: cULus

- Voltage rating: 125V
- Current rating: 4A
- Wire range:
- Solid wire(AWG): 20-28
- Stranded wire(AWG): 20-28
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -33°C to +105°C

POLE		2	3	4	5	6	7	8	9	10	11	12
A		5.60	8.10	10.60	13.10	15.60	18.10	20.60	23.10	25.60	28.10	30.60
B		2.50	5.00	7.50	10.00	12.50	15.00	17.50	20.00	22.50	25.00	27.50
Tol.		±0.10					±0.15					
POLE	13	14	15	16	17	18	19	20	21	22	23	24
A	33.10	35.60	38.10	40.60	43.10	45.60	48.10	50.60	53.10	55.60	58.10	60.60
B	30.00	32.50	35.00	37.50	40.00	42.50	45.00	47.50	50.00	52.50	55.00	57.50
Tol.		±0.20					±0.30					

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X, ±

UNIT / mm

SCALE 1 : 1

.XX, ±


DATE

.XXX, ±

ANG, ±

SIZE A4

PPOJECTION



ORDER INFORMATION

TBX025-SVB-xx-LF

SERIES | LEADFREE
| 02-24WAY
| BOTTOM SIDE
| SCREW 180°
| FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: