

Material and Finish

- Housing: PBT (UL94V-0), Black.
- Terminal: Sq. 0.46mm Brass, Gold Plating on Contact Area, Tin Plating on Solder Tail.

Electrical Characteristics

- Current Rating: 1.0 Amp. Max..
- Dielectric Withstand Voltage: 600V AC RMS for 60Seconds.
- Insulation Resistance: 1000M Ohms Min. at 500V DC.

Mechanical Characteristics

- Operating Temperature: -55°C ~ +105°C

Dimensions					Dimensions				
Pos.	A	B	C	D	Pos.	A	B	C	D
10	26.15	15.28	12.86	5.08	44	47.74	36.87	34.45	26.67
16	29.96	19.09	16.67	8.89	50	51.55	40.68	38.26	30.48
20	32.50	21.63	19.21	11.43	60	57.90	47.03	44.61	36.83
26	36.31	25.44	23.02	15.24	68	62.98	52.11	48.96	41.91
30	38.85	27.98	25.56	17.78	70	64.25	53.38	50.96	43.18
34	41.39	30.52	28.10	20.32	80	70.60	59.73	57.31	49.53
40	45.20	34.33	31.91	24.13	100	83.30	72.43	70.01	62.23

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE


SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION



ORDER INFORMATION



煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 1.27*2.54mm Box Header Ejector Type PCB Mount Vertical With Long Latch