

NOTES:

1.MATERIAL

1.1 Insulator:PBT+30%Glass Fiber(UL94V-0)

BLACK

1.2 Contact:Brass

1.3 Contact Plated:Gold/Tin Plated

1.4 Shell:Steel,Nickel Plated

1.5 Screw:Brass, Nickel Plated

2.SPECIFICATION

2.1 Current Rate: 3 Amps

2.2 Insulator Resistance: 1000M $\Omega$  Min At 500V DC

2.3 Dielectric Strength: 500V Per minute

2.4 Operation Temperature: -40°C to+85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X,  $\pm$   
.X  $\pm$  0.38  
.XX  $\pm$  0.25  
.XXX  $\pm$  0.15  
ANG  $\pm$  2°



ORDER INFORMATION

DR-PSN-09-LF  
SERIES | NUT | SEMI GOLD | MALE  
LEADFREE  
09 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DR9 掃摺 8.1 RoHS