

Recommended P.C.B Layout

MATERIAL

Insulator : 30% Glass fiber PBT
 Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ±
 ANG ± 3°

PPOJECTION



ORDER INFORMATION

HS-D128038030T-1Xxx-LF
 SERIES | | | | | LEADFREE
 DIP 180° | | | | | 1X02:02 WAY
 TOTAL 12.8mm | | | | | 1X40:40 WAY
 | | | | | TIN
 | | | | | DIP 3.0mm
 | | | | | CONTACT 3.8mm

DESCRIPTION: PIN HEADER 2.54*2.54mm STRAIGHT STACK