

### Specifications


Current Rating: 1Amp  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding: 300V AC/DC  
 Contact Resistance: 20mΩ Max.  
 Operating Temperature: -40°C to +105°C

### Materials

Contact Material: Copper Alloy  
 Insulation Material: Polyester, UL 94V-0  
 Nylon 6T

Recommended

Hole Layout P.C.Board



RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

P PROJECTION

X, ±  
 .X ± 0.38  
 .XX ± 0.25  
 .XXX ± 0.13  
 ANG ±



### ORDER INFORMATION

PA-R20153823-2Xxx-LF  
 SERIES | LEADFREE  
 2X02:04WAY  
 2X50:100WAY  
 DIP 90° | DIP 2.3mm  
 BASE 2.0mm | CONTACT 3.8mm  
 R/A1.5mm

DESCRIPTION: 1.27 PIN HEADER DUAL ROWS (R/A) TYPE BASE 1.7H