


1. MATERIALS :

- a. BODY : ZINC ALLOY, DIE CASTIN NICKEL PLATED.
  - b. CONTACT: BRASS NICKEL PLATED.
  - c. BRACKET: A.B.S.
  - d. INSULATOR: ENGINEER PLASTIC POM .
2. NOMIAL IMPEDENCE 50(75)OHMS.  
 3. FREOUENCY RANGE: 0-2 GHZ.  
 4. MAX PEAK VOLTAGE: 500V  
 5. DIELECTRIC STRENGTH WITHSTAND 1.5KV NNS.



RoHS Compliant

TOLERANCES ARE

0.5-5	=±0.2
5-30	=±0.4
30-120	=±0.6
120-315	=±1
315-1000	=±1.6
1000-2000	=±2.4

DRAWING BY CY	
CHECKED BY GENIUS	
UNIT / mm	SCALE 1 : 1
DATE	
SIZE A4	PPOJECTION

ORDER INFORMATION

BNCA3-JRE2-xx-LF

SERIES	LEADFREE
	50:50 OHM
	75:75 OHM
	EAR
	DIP 90°
	JACK

DESCRIPTION: BNC FEMALE R/A 1\*3 PORT

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com