

MATERIAL

INSULATOR: GLASS-REINFORCED THERMOPLASTIC (PBT),
UL94V-0 RATED.

CONTACT: COPPER ALLOY.

SOLDER AREA- 120u TIN 50u NICKEL.

COLOR:GREEN

ELECTRICAL

DIELECTRIC WITHSTANDING VOLTAGE: 1,000 VAC RMS.

CURRENT RATING: 3 AMP.

INSULATION RESISTANCE: 5,000 MEG. OHMS MIN. AT 500 VDC.

CONTACT RESISTANCE: 20 MILLI OHMS MAX.

MECHANICAL

INSERTION FORCE: 340 GRAMS MAX PER CONTACT PAIR.

WITHDRAWAL FORCE: 28 GRAMS MIN PER CONTACT PAIR.

ENVIRONMENTAL

TEMPERATURE RANGE: -55° TO +85°.

Pin NO. \ DIM.	A	B	C	D	E
06	29.94	22.22	14.74	10.34	5.08
14	40.10	32.38	24.9	20.50	15.24
16	42.64	34.92	27.44	23.04	17.78
66	106.14	98.42	90.94	86.54	81.28
86	131.54	123.82	116.34	111.94	106.68
100	149.32	141.60	134.12	129.72	124.46

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

GE-SLE-xxx-LF
SERIES | LEADFREE
006~100WAY
LOW EARS
SOLDER

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: