



**NOTE:**

**MATERIAL:**  
 UPPER COVER-ABS  
 BOTTOM COVER-ABS  
 SHIELD-SUS301/T=0.15mm  
 HOUSING -PA66+30%G.F.  
 LATCH-SUS 301/T=0.50mm  
 TERMINAL-JIS C5210/T=0.20mm

**TERMINAL PLATING:**  
 50~80U" Ni UNDER PLATE A11 OVER.  
 80~120U" Sn IN TAIL AREA.  
 Min 8U"GOLD PLATED IN CONTACT AREA

**ELECTRICAL**  
 CURRENT RATING:0.5A  
 DIELECTRIC WITHSTANDING VOLTAGE:300VAC  
 INSULATION RESISTANCE:100MΩ /1000VDC  
 CONTACT RESISTANCE:80mΩ

**ENVIRONMENTAL**  
 OPERATING TEMPERATURE:-10°C TO 60°C  
 STORAGE TEMPERATURE:-30°C TO 60°C

注: |A-A| ≤ 0.08  
 |B-B| ≤ 0.10

NO.	DRAWING NO.	NAME	MATERIAL	COLOR	QTY
1	CAA-1057-BKA	DELL X50 36P Upper Cover	ABS	BLACK	1PCS
2	CAA-1058-BKA	DELL X50 36P Bottom Cover	ABS	BLACK	1PCS
3	SEE-0349-Y*A	DELL X50 36P SHIELD	SUS301		2PCS
4	LEE-0310-Y*A	ML 24P LATCH-R	SUS301		1PCS
5	LEE-0311-Y*A	ML 24P LATCH-L	SUS301		1PCS
6	EEF-0031-J*A	TPF2.0X6ABK尖尾螺絲	中碳鋼		2PCS
7	SADL-X50*01M	DELL X50 36P Housing Assembly			1SET

**RoHS Compliant**

TOLERANCES ARE



DRAWING BY CY		X, ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PJECTION	



**ORDER INFORMATION**

CDMA-PA-36-LF  
 SERIES | LEADFREE  
 36 WAY  
 ASSEMBLY  
 MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: