



### RECOMMENDED FOOTPRINT

NO.	DESCRIPTION	MATERIALS	FINISHED
1	BODY	BRASS	Gold
2	CONTACT	Be. Copper	Gold 30 μ"
3	INSULATOR	TEFLON	

### ELECTRICAL PERFORMANCE :

IMPEDANCE : 50 OHMS

FREQUENCY : DC-12.4GHz

WORKING VOLTAGE : 500 VRMS MAX.

DIELECTRIC WITHSTANDING VOLTAGE : 1000 VRMS MAX.

INSULATOR RESISTANCE : 5000 MEGOHMS MIN.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司

DRAWING BY CY

X. ± 0.20

CHECKED BY GENIUS

.X ± 0.10

UNIT / mm

SCALE 1 : 1

.XX ± 0.05

DATE

.XXX ±

ANG ±

SIZE A4

P PROJECTION



### ORDER INFORMATION

SMA-JV-50-LF  
SERIES | LEADFREE  
50 WAY  
180°SMT  
JACK

www.morethanall.com

DESCRIPTION: SMA Female S/T for Surface Mount