



(DB15M/HD15F ADAPTOR)

PIN OUT: 15Male	15Female
1, shell	4,5,6,7,8,10,11 shell
2	1
4, shell	4,5,6,7,8,10,11 shell
5	2
6, shell	4,5,6,7,8,10,11 shell
7	DIODE
9	3
12	14
13	4,5,6,7,8,10,11 shell
15	13

Label: orange color with white character  
 One side: VGA ADAPTOR HD15/DB15  
 The other side: VGA ADAPTOR HD15/DB15  
 SPECIFICATION  
 INSULATOR: PBT Glass fibre reinforced UL 94 VO  
 CONTACT: Brass  
 CONTACT PLATING: Gold plated over nickel  
 SHELL: Tin plated shell  
 CURRENT RATING: 3 AMP  
 DIELECTRIC STRENGTH: 500V AC for one minute  
 INSULATOR RESISTANCE: 500MΩ min at 500V DC  
 TEMPERATURE: -25°C — +105°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
 煜倫股份有限公司  
 www.morethanall.com

DRAWING BY CY		X, ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PPOJECTION	



ORDER INFORMATION

DBHD-ES-1515-LF	
SERIES	LEADFREE
15 TO 15 WAY	
MALE TO FEMALE	

DESCRIPTION: