



T:1.6 Dimensions of PC board holes

Tolerance : ±0.1(Printed-top view)

LEAD FREE

| | | | | | | | |
|-----|----------------|-----|----------|-------|--------|-------|--------|
| 6 | EARTH TERMINAL | 2 | C2680 | t=0.5 | MB:Cu | Cu/Sn | PLATED |
| 5 | WASHER | 6 | ABS | | | | |
| 4 | HOUSING | 1 | ABS | | | | |
| 3 | OUTER CONTACT | 6 | C2680 | t=0.5 | MB:Cu | Ni | PLATED |
| 2 | TERMINAL | 3 | C2680 | t=0.5 | MB:Cu | Cu/Sn | PLATED |
| 1 | TERMINAL | 3 | C2680 | t=0.5 | MB:Cu | Cu/Sn | PLATED |
| LTR | PART NAME | QTY | MATERIAL | | REMARK | | |

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

RCAB3-JR115E2xxx14-03-LF

SERIES | | | | | | LEADFREE
| | | | | | 03 WAY
| | | | | | 14mm
| | | | | | EAR
| | | | | | 11.5mm
| | | | | | DIP 90°
| | | | | | JACK
COLOR A.B.C.D.E.F

DESCRIPTION: PIN JACK

www.morethanall.com