

P.B.C LAYOUT  
BOTTOM VIEW

Insulator Color Code:(A → B → C) Δ

|       |       |        |        |      |
|-------|-------|--------|--------|------|
| 1     | 2     | 3      | 4      | 5    |
| Black | Red   | White  | Yellow | Blue |
| 6     | 7     | 8      | 9      |      |
| Gray  | Green | Orange | Brown  |      |

| SCHEMATIC |               |      |          |        |       |
|-----------|---------------|------|----------|--------|-------|
|           |               |      |          |        |       |
| 5         | TIP SHUNT     | 3    | BRASS    | Sn/Cu  |       |
| 4         | HOUSING       | 1    | PBT      |        | BLACK |
| 3         | WASHER        | 3    | PBT      |        |       |
| 2         | TIP           | 3    | P.B.S    | Sn/Cu  |       |
| 1         | OUTER CONTACT | 3    | SPCC Δ   | NICKEL |       |
| NO        | PART NAME     | Q'TY | MATERIAL | PLATED | COLOR |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±  
.X ± 0.20

CHECKED BY GENIUS

.XX ± 0.10

UNIT / mm

SCALE 1 : 1


.XXX ±

DATE

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

RCAA3-JR40E0xxx-03-LF

SERIES JACK LEADFREE  
03 WAY  
COLOR A.B.C  
NON EAR  
4.0mm  
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: RCA JACK