

### Performance:

Meets C3 Standard.

### Materials:

Body : Fireproof ABS UL-94V0  
 Jack : 6P6C 6 micro inches gold plated  
 PCB : FR-4 / UL-94V0  
 IDC Body : Fireproof ABS UL-94V0  
 IDC Pin : Bronze & Tinned

IDC Description : For 22-26 AWG.  
 For Krone punch-down Tool

### Electrical Specifications:

Insulation Resistance : 500M ohms (min.)  
 Contact Resistance : 20m ohms (max.)  
 Current Rating : 1.5 Amps .  
 DC Resistance : 0.1 ohms (max.)  
 Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

### Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)  
 Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 1.00


.X ± 0.20

.XX ± 0.15

.XXX ±

ANG ±

PJECTION



### ORDER INFORMATION

MJK16-TWP06-0606-LF

SERIES | | | | LEADFREE  
 | | | | 6P6C  
 | | | | 06u" GOLD  
 | | | | PLASTIC  
 | | | | WHITE  
 | | | | IDT

DESCRIPTION: C3 KEYSTONE JACK UTP 6u