

NOTE:

1. TEMPERATURE RANGE: -55°C TO +125°C
2. CURRENT RATING: 20°C 2A, 70°C 1A, 100°C 0.5A
3. CONTACT RESISTANCE: 30 MILLIOHMS MAX. AT DC100mA
4. DIELECTRIC VOLTAGE: AC 1110V FOR 1 MINUTE
5. INSULATION RESISTANCE: 1000 MEGOHMS MIN. AT DC500V
6. OPERATING VOLTAGE: 251VAC

③	OPTIONAL	BOARD-LOCK : BRASS, 100u" MIN. TIN PLATING
②	NO. OF POS.	CONTACT : BRASS, NICKEL PLATING OVER ALL AT 50 u" MIN. SOLDER AREA PLATING: 100u" MIN. TIN, CONTACT AREA PLATING GOLD
①	1	HOUSING : PBT UL94 V-I, COLOR GRAY
ITEM	Q'TY	DESCRIPTION

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
**煜倫股份有限公司**

DRAWING BY CY


CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±  
.X ± 0.30  
.XX ± 0.25  
.XXX ±  
ANG ±



**ORDER INFORMATION**

UC-PR-2X32-LF  
SERIES | LEADFREE  
64WAY  
DIP 90°  
MALE

DESCRIPTION:

[www.morethanall.com](http://www.morethanall.com)