



無鼻型 (6 / 8 / 10 / 12 PIN G處只有一邊有凹槽，  
14及14PIN以上G處兩邊都有凹槽)

**\*Material:**

Insulator: PBT+Glass Fiber (UL94V-0).  
Contact: Copper Alloy.  
Contact Plated: Gold or Tin over Nickel Plated.  
All material accord with ROHS。

**\*Specification:**

Withstanding Voltage: AC 500V for 1 Minute.  
Insulation Resistance: 1000MΩ Min. at DC 500V.  
Contact Resistance: 30Ω Max..  
Operating Temperature: -40°C ~ +105°C.

**備注:**

- 1.加反折為3件式，不加反折為2件式。
- 2.未標示公差之尺寸參考公差表。

| Pos. | Dim. A | Dim. B | Dim. C | Dim. D | Dim. E |
|------|--------|--------|--------|--------|--------|
| 6    | 12.32  | 6.35   | 5.08   | 12.12  | 1.9    |
| 8    | 14.86  | 8.89   | 7.62   | 14.66  | 1.9    |
| 10   | 17.40  | 11.43  | 10.16  | 17.20  | 3.8    |
| 12   | 19.94  | 13.97  | 12.70  | 19.74  | 3.8    |
| 14   | 22.48  | 16.51  | 15.24  | 22.28  | 3.8    |
| 16   | 25.02  | 19.05  | 17.78  | 24.82  | 3.8    |
| 18   | 27.56  | 21.59  | 20.32  | 27.36  | 3.8    |
| 20   | 30.10  | 24.13  | 22.86  | 29.90  | 3.8    |
| 24   | 35.18  | 29.21  | 27.94  | 34.98  | 3.8    |
| 26   | 37.72  | 31.75  | 30.48  | 37.52  | 3.8    |
| 30   | 42.80  | 36.83  | 35.56  | 42.60  | 3.8    |
| 34   | 47.88  | 41.91  | 40.64  | 47.68  | 3.8    |
| 40   | 55.50  | 49.53  | 48.26  | 55.30  | 3.8    |
| 44   | 60.58  | 54.61  | 53.34  | 60.38  | 3.8    |
| 50   | 68.20  | 62.23  | 60.96  | 68.00  | 3.8    |
| 60   | 80.90  | 74.93  | 73.66  | 80.70  | 3.8    |
| 64   | 85.98  | 80.01  | 78.74  | 85.78  | 3.8    |

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30

.X ± 0.20

.XX ± 0.10

.XXX ± 0.05

ANG ±

PPOJECTION



**ORDER INFORMATION**

F-C3X-xx-LF  
SERIES | LEADFREE  
06~64WAY  
NON NOSE  
THREE TYPE

**煜倫股份有限公司**

www.morethanall.com

DESCRIPTION: