

Material

- Item a Clamp: Brass(CuZn) Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact: PhBz, Tin plated
- Item d Terminal (housing): Thermoplastic (UL94V-0)
- Item e Terminal (cover): Thermoplastic (UL94V-0)

$\triangle \triangle$ Electrical cULus/VDE

- Voltage rating: 300VAC/125VAC
- Current rating: 10A/10.5A
- Wire range: 1.5mm²
- Solid wire(AWG): 16-26/16-26
- Stranded wire(AWG): 16-26/16-26
- Torque: 3Lb-In/0.2Nm
- Screw: M2
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV
- \triangle ● Operating temperature: -40°C to +115°C
- Safety Approval:

N = Number of poles
 Dim A = N x 3.81
 Dim B = (N - 1) x 3.81

	Dim A	Dim B
2-6p	± 0.15	± 0.15
7-12p	± 0.20	± 0.20
13-18p	± 0.25	± 0.25
19-24p	± 0.30	± 0.30

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X, \pm
 .X \pm
 .XX \pm
 .XXX \pm
 ANG \pm

PJECTION



ORDER INFORMATION

TBH038-SWCEE-xx-LF

SERIES | LEADFREE
 | 02-12WAY
 | EMPTY EVEN PIN
 | CAGE
 | SCREW WIRE
 | FEMALE

DESCRIPTION: