

RECOMMENDED PCB LAYOUT

NOTE :

- * Material : Nylon UL 94V-0
- * Standard Color :White
- * .023" (0.60mm) square pins
- * Tin plated brass pins
- * Current rating : 3A, AC/DC
- * Voltage rating : 250V, AC/DC
- * 8-40 circuits available

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
8	7.50	15.00	26	30.00	37.50
10	10.00	17.50	28	32.50	40.00
12	12.50	20.00	30	35.00	42.50
14	15.00	22.50	32	37.50	45.00
16	17.50	25.00	34	40.00	47.50
18	20.00	27.50	36	42.50	50.00
20	22.50	30.00	38	45.00	52.50
22	25.00	32.50	40	47.50	55.00
24	27.50	35.00			

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 2°

PPOJECTION



ORDER INFORMATION

XAD-DX-xx-LF
SERIES | LEADFREE
08-40 WAY
NON POST
DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: