

PCM-PA-32-LF  
LEADFREE

RoHS Compliant

備註/NOTE :

1. 安規/SAFETY :

- 1-1. 規格/RATING : 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗/INSULATION RESISTANCE : 200MΩ MIN at 250V DC
- 1-3. 絕緣耐壓/WITHSTANDING : 250V AC at 1 MINUTE
- 1-4. 接觸阻抗/CONTACT RESISTANCE : 50mΩ MAX AT DC 1A

2. 材質/MATERIAL :

- 2-1. 膠芯/HOUSING : PBT 30% GF-94V0
- 2-2. 針/PIN : 磷銅/PHOSPHOR BRONZE
- 2-3. 上線夾/PLASTIC UP COVER : PBT 30% GF-94V0

- 2-4. 下線夾/PLASTIC DOWN COVERN : PBT 30% GF-94V0
- 2-5. 外套/PLASTIC COVER : NYLON1 15% GF UL94-V0
- 2-6. 上蓋/METAL UP COVER : 不鏽鋼
- 2-7. 下蓋/METAL DOWN COVER : 不鏽鋼/STAINLESS
- 2-8. 線夾/CABLE FIXED : 不鏽鋼/STAINLESS

3. 電鍍/PLATING :

- 3-1. 針/PIN:CONTACT AREA : GOLD 5u"  
SOLDER ARES : TIN-LEAD 100u"MIN

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO. PCM-PA-32

DWG NO. PCM-PA-32

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIPTION: PCMCIA 32PIN (F)成品

AREA

REVISIONS

HK

DATE

焜倫股份有限公司