



SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 100V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 6T,UL94V-0

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
ZHQ-V-02	1.50	4.30
ZHQ-V-03	3.00	5.80
ZHQ-V-04	4.50	7.30
ZHQ-V-05	6.00	8.80
ZHQ-V-06	7.50	10.30
ZHQ-V-07	9.00	11.80
ZHQ-V-08	10.50	13.30
ZHQ-V-09	12.00	14.80
ZHQ-V-10	13.50	16.30
ZHQ-V-11	15.00	17.80
ZHQ-V-12	16.50	19.30
ZHQ-V-13	18.00	20.80
ZHQ-V-14	19.50	22.30
ZHQ-V-15	21.00	23.80

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. **ZHQ-V-xx**

DWG NO. **ZHQ-V-xx**

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X±0.2
.XX±
.XXX±
AWG

DESCRIPTION:

1.50mm PITCH 180° WAFER-SMT TYPE

AREA	REVISIONS	HK	DATE
------	-----------	----	------