


1. MATERIALS AND FINISH
 - 1.1 HOUSING MATERIALS: THERMOPLASTIC.
 - 1.2 CONTACTS: COPPER ALLOY. UNDER PLATING NICKEL. CONTACT AREA PLATING G/F.
2. SPECIFICATIONS
 - 2.1 CURRENT RATING: 0.5A MAX.
 - 2.2 INSULATION RESISTANCE: 1000MΩ MIN.
 - 2.3 DIELECTRIC WITHSTANDING VOLTAGE: 300V (r.m.s) AC FOR 1 MINUTE.
 - 2.4 CONTACT RESISTANCE: mΩ30 MAX.
 - 2.5 OPERATING TEMPERATURE: +85°C ~ -40°C.

68	73.20[2.882]	69.10[2.720]	66.00[2.598]
64	69.20[2.724]	65.10[2.563]	62.00[2.441]
60	65.20[2.567]	61.10[2.406]	58.00[2.283]
50	55.20[2.173]	51.10[2.012]	48.00[1.890]
44	49.20[1.937]	45.10[1.776]	42.00[1.654]
40	45.20[1.780]	41.10[1.618]	38.00[1.496]
36	41.20[1.622]	37.10[1.461]	34.00[1.339]
34	39.20[1.543]	35.10[1.382]	32.00[1.260]
30	35.20[1.386]	31.10[1.224]	28.00[1.102]
26	31.20[1.228]	27.10[1.067]	24.00[0.945]
24	29.20[1.150]	25.10[0.988]	22.00[0.866]
22	27.20[1.071]	23.10[0.909]	20.00[0.787]
20	25.20[0.992]	21.10[0.831]	18.00[0.709]
18	23.20[0.913]	19.10[0.752]	16.00[0.630]
16	21.20[0.835]	17.10[0.673]	14.00[0.551]
14	19.20[0.756]	15.10[0.594]	12.00[0.472]
12	17.20[0.677]	13.10[0.516]	10.00[0.394]
10	15.20[0.598]	11.10[0.437]	8.00[0.315]
6	11.20[0.411]	7.10[0.280]	4.00[0.157]
Number Of Position	A	B	C
	DIMENSIONS		



MF-C2X-xxx-LF
LEADFREE
RoHS Compliant



PART NO. MF-C2X-xxx	
DWG NO. MF-C2X-xxx	
FILE NO.	
UNIT / mm	SCALE 1:1

APPROVED BY CY	TOLERANCES ARE .X ±0.3 .XX ±0.2 .XXX AWG
DRAWING BY	
PROJECTION	

DESCRIPTION:	IDC SOCKET 2.00PH KIT BLACK (WITHOUT NOSE)			
AREA	REVISIONS	HK	DATE	

煜倫股份有限公司