

RECOMMENDED P. C. B. LAYOUT

### SPECIFICATIONS

#### ELECTRICAL CHARACTERISTICS:

Contact Current Rating:3 Amperes.  
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.  
 Insulation Resistance:5000 Medohms Minimum.at DC 500V.  
 Contact Resistaance:25 Milliohms Maximum.  
 Operating Temperature:-55°C to+105°C.

#### MECHANICAL CHARACTERISTICS:

Contact Insertion Force:341 g.Maximum.  
 Contact Seperation Force:21 g.Minimum.

#### MATERIALS:

Contacts:Brass.  
 Insulator: PBT UL 94V-0 Rated.  
 Shell: Cold Roller Steel.

#### FINISHES:

Contact:Gold Flash.  
 Shell:Nickel Plated.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±



#### ORDER INFORMATION

HDR30-SSNJBL-15-LF  
 SERIES | | | | LEADFREE  
 FEMALE | | | | 15WAY  
 NUT | | | | BLUE  
 SEMI GOLD | | | | JACKSCRW

DESCRIPTION: **MINI BODY D-SUB CONNECTOR 0.121"(3.08mm) FOOTPRINT,RIGHT ANGLE**

煜倫股份有限公司

www.morethanall.com