


⚠ Specifications

Current Rating: 3Amp  
 Insulation Resistance: 1000MΩMin.  
 Dielectric Withstanding Voltage: 600VAC  
 Contact Resistance: 20mΩMax.  
 Operating Temperature: -40°C to +105°C  
 Materials  
 Contact Material: Phosphor Bronze  
 Insulator Material: Thermoplastic, UL 94V-0  
 PBT or the equivalent material

Recommended P.C.Board  
 Layout  
 (Tolerance: ±0.05)



RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PPOJECTION

X ± 0.30  
 X ± 0.25  
 .XX ± 0.15  
 .XXX ± 0.10  
 ANG ±



ORDER INFORMATION

FK-RK-2Xxx-LF

SERIES | LEADFREE  
 2X03:06 WAY  
 2X36:72 WAY  
 KEY  
 DIP 90°

DESCRIPTION: 2.54 FEMALE HEADER DUAL ROWS (R/A) TYPE BASE 8.5H