

DIMENSION

A	$(N-1) \times 3.5 + 4.3$
B	$(N-1) \times 3.5$

N=Number of contacts

Technical Data

Material:

- Contact|metal housing| Brass Machined|Option|
- Terminal screw Steel Galvanized and chromated or Nickel plated or Tin plated|standard|option|

- ⚠ ● Wire guard: PhBz, Tin plated
- Insulator body|housing| Polyamide|Glass filled|UL 94V-0|

- Electrical**
- Voltage rating 300VAC
 - Current rating: 8 Amps/way max
 - Contact resistance: $21m\Omega$ max|
 - Insulation resistance $500M\Omega/1000V$

- ⚠ ● Withstanding Voltage 2500VAC|1min| Test time=60sec/1pcs
- Wire range: 16-28AWG

Mechanical:

- Torque 2kg-cm/M2
- ⚠ ● Operating temperature: $-41^{\circ}C$ to $+121^{\circ}C$
- Soldering temperature= $250^{\circ}C/5$ seconds max

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±


.X, ±

.XX, ±

.XXX, ±

ANG, ±

PPOJECTION



ORDER INFORMATION

TBH035-SVCA-xx-LF

SERIES | | | | LEADFREE
| | | | 02-24WAY
| | | | UPPER SIDE
| | | | CAGE
| | | | SCREW 180°
| | | | FEMALE

DESCRIPTION: