

\*\*\*CONSTRUCTION:

1.CABLE: \* UL2464 (2C/16#)+A OD:6.0mm BLACK JACKET.

\*\*\*CONNECTORS:

2.CONNECTOR: \* PITCH 5.0MM 6PIN TERMINAL BLOCKS Dinkle P/N TBH050-SW-06

3.TERMINAL: \* TUBULAR TERMINAL (CET-1508-BK ).

\* WIRE SIZE:1.5mm<sup>2</sup>/16AWG LENGTH:10mm.

\* INSULATED: NYLON(BLACK).

\* COPPER WITH TIN PLATED.

4.TEST: \* CT: 2 Ohm. IS: 5M Ohm.

5.PACKING: \* PACK EACH CABLE IN A POLY BAG.

6.MATERIAL: \* MATERIAL WITH RoHS GRADE.

PIN OUT

P1

1 — BLUE — T1

2 — BROWN — T2

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

CETTBHX21-100616-F80C-LF

SERIES

LEADFREE  
800mm  
FEMALE  
16 AWG  
10mm TO 06 WAY

DESCRIPTION: PITCH 5.0MM 6PIN TERMINAL BLOCKS TO TUBULAR TERMINAL