

NOTES:

PLATING:

TERMINAL: 50~80U" NI UNDER PLATE All
OVER. MIN 3U"GOLD PLATED IN CONTACT AREA

ELECTRICAL SPECIFICATION:

CURRENT RATING: 0.8A
VOLTAGE RATING: 250VAC
WITHSTANDING VOLTAGE: MIN 300VAC
INSULATION RESISTANCE: MIN 100MΩ
CONTACT RESISTANCE: MAX 80mΩ

ENVIRONMENTAL

OPERATING TEMPERATURE: -15°C TO +85°C
STORAGE TEMPERATURE: -30°C TO +85°C

TOLERANCE					
	X.	X.X	X.XX	X.XXX	X.°
A	±0.20	±0.10	±0.05	±0.03	±1°
B	±0.50	±0.20	±0.10	±0.05	±2°
✓ C	±0.80	±0.40	±0.20	±0.10	±3°

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

IPD-JW-30-LF
SERIES T LEADFREE
30 WAY
90°SMT
JACK

DESCRIPTION: I POD 30P SOCKET