



$\phi 1.3\text{min} \times 4$
 $\phi 1.0\text{min} \times 1$
 PCB MOUNTING HOLE

ELECTRICAL :	
IMPEDANCE :	75Ω
FREQUENCY :	0 TO 4.0 GHz
VSWR:	1.4 Max
RETURN LOSS:	≥ 15dB, 0.5 to 4 GHz

NO	DESCRIPTION	Q'TY	ITEM NO.	MATERIAL	PLATING
1	BODY 1	1	12-P225-7C-HI-ROHS	BRASS	SILVER
2	BODY 2	1	12-P225-7C-HI-ROHS	BRASS	GOLD 3-
3	DIELECTRIC 1	1	T-040273	TEFLON	-
4	DIELECTRIC 2	1	T-060998	TEFLON	-
5	CENTER PIN	1	12-P225-7C-HI-Be3	BERYLLIUM COOPER	GOLD 3-
6	PARTS	1	R-06002-ROHS	BRASS	GOLD 3-

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION



ORDER INFORMATION

1656-JR-75-LF
 SERIES | LEADFREE
 | 75 OHM
 | DIP 90°
 JACK

DESCRIPTION: