



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55°C TO +105°C.

MECHANICAL CHARACTERISTICS:

CONTACT INSERTION FORCE: 4.0 KG MAXIMUM.
 CONTACT SEPARATION FORCE: 0.5 KG MINIMUM.

MATERIALS:

CONTACT: PHOSPHOR BRONZE.
 INSULATOR: NYLON 6T
 SHELL: STAINLESS.
 HOOD: NYLON66+15GF

FINISHES:

CONTACTS: GOLD FLASHED 10U", 15U", 20U", 30U".

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MSB-PA-4H

DWG NO. MSB-PA-4H

FILE NO.

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X
.XX
.XXX
AWG

DESCRIPTION:

MINI U.S.B. 4PIN(M) (HRS) 裝配式 (單面防呆)

AREA

REVISIONS

HK

DATE

焜倫股份有限公司

UNIT / mm

SCALE 1:1

