



3. 尺寸规格图

MISW-D87-28-LF  
LEADFREE  
RoHS Compliant

类 型	压接微动开关	品 名	MISW-D8T-28
1. 功能规格			
1.1额定电压	125/250VAC	1.6自由位置 (FP)	15.0±1.5mm
1.2额定电流	5A	1.7动作位置 (OP)	12.4±1.3mm
1.3接触电阻(CR)	≤50mΩ (初始值)	1.8行程 (PT)	
1.4操作力 (OF)	28±12gf	1.9灵敏度 (BT)	
1.5回弹力 (RF)		1.10	
2. 可靠度参数			
2.1机械寿命	1,000,000 CYCLES	2.5焊接工艺	手工焊
2.2电气寿命	10,000 CYCLES	2.6操作温度	-25° C - +85° C
2.3绝缘电阻(IR)	≥100MΩ DC500V (初始值)	2.7储存湿度	<85%RH
2.4耐压强度 (WV)	AC1000V 1 minute(初始值)	2.8	

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO. MISW-D87-28

DWG NO. MISW-D87-28

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIP TION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司