



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30m ohm Min.
 Insulation Resistance: 1000 M OHM Min.
 Withstanding Voltage: 650V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
DF3-H-02	2.00	6.00
DF3-H-03	4.00	8.00
DF3-H-04	6.00	10.00
DF3-H-05	8.00	12.00
DF3-H-06	10.00	14.00
DF3-H-07	12.00	16.00
DF3-H-08	14.00	18.00
DF3-H-09	16.00	20.00
DF3-H-10	18.00	22.00
DF3-H-11	20.00	24.00
DF3-H-12	22.00	26.00
DF3-H-13	24.00	28.00
DF3-H-14	26.00	30.00
DF3-H-15	28.00	32.00

DF3-H-xx-LF
 LEADFREE
 RoHS Compliant



煜倫股份有限公司

PART NO. DF3-H-xx		CHECKED BY CY		TOLERANCES ARE .X±0.2 .XX± .XXX± AWG	DESCRIP TION:	AREA	REVISIONS	HK	DATE
DWG NO. DF3-H-xx		DRAWING BY							
FILE NO.		PROJECTION							
UNIT / mm	SCALE 1:1								