



RECOMMENDED P.C.BOARD HOLE DIMM.



### SPECIFICATIONS

#### Electrical

- Current Rating: 5A AC, DC
- Voltage Rating: 250V AC, DC
- Operating Temp.: -25°C ~ +85°C
- Insulation Resistance: 1000MΩ / min.
- Dielectric Withstanding Voltage: 1500V AC / min.
- Contact Resistance: 10mΩ / max.

#### Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
2	3.96	7.92	KK-DRP-02	
3	7.92	11.88	KK-DRP-03	
4	11.88	15.84	KK-DRP-04	
5	15.84	19.80	KK-DRP-05	
6	19.80	23.76	KK-DRP-06	
7	23.76	27.72	KK-DRP-07	
8	27.72	31.68	KK-DRP-08	
9	31.68	35.64	KK-DRP-09	
10	35.64	39.60	KK-DRP-10	
11	39.60	43.56	KK-DRP-11	
12	43.56	47.52	KK-DRP-12	

KK-DRP-xx-LF  
LEADFREE

RoHS Compliant

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO. KK-DRP-xx		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION: 3.96mm Wire-to-Board Header Dip 180° Type		
DWG NO. KK-DRP-xx					DRAWING BY	
FILE NO.		PROJECTION	AREA	REVISIONS	HK	DATE
UNIT / mm	SCALE 1:1					

煜倫股份有限公司